# RUSH+ PANORAMIC AND SPORTY

The RUSH + adopts an ultra-sporty design with its co-injected and ultra-flexible temples ... and is 100% customisable.







Non-slip adjustable bridge



RUSHPFSPSI (Rush+ clear with foam & strap)



Fully customise the RUSH +: lens marking, temples colour ... Informations & conditions : marketing@bolle-safety.com

- **+** UPPER PROTECTION
- + CO-INJECTED, ULTRA-FLEX TEMPLES
- **+** NON-SLIP ADJUSTABLE BRIDGE
- **+** BI-COLOUR TEMPLES DEPENDING ON VERSION



RUSHPPSI

RUSHPPSI

RUSHPT

RUSHPPSIB

RUSHPPSIG

RUSHPPSIC

RUSHPPSIY

RUSHPPSE

RUSHPCSE

RUSHKITFS

Kit foam & strap

PSPRUS+-S01 Strap only

# RUSH+ **PANORAMIC AND SPORTY**

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
	Clear	RUSHPPSI 📕	2C-1,2 🗁 1 FT KN CE	🗁 EN166 FT <b>C €</b>	Anti-scratch/Anti-fog +
	RUSH+ with foam & strap	RUSHPFSPSI	2C-1,2 🖼 1 FT KN CE	🗁 EN166 FT <b>C €</b>	Anti-scratch/Anti-fog 구
	Smoke	RUSHPPSF	5-3,1 🗁 1 FT KN CE	🗁 EN166 FT <b>C €</b>	Anti-scratch/Anti-fog +
	Smoke	RUSHPPSFY 🖌	5-3,1 🗁 1 FT KN CE	🗁 EN166 FT CE	Anti-scratch/Anti-fog +
	CSP	RUSHPCSP	5-1,4 🗁 1 FT KN C€	🗁 EN166 FT <b>C €</b>	Anti-scratch/Anti-fog +7
RUSH+	TWILIGHT	RUSHPTWI	5-2 🗁 1 FT KN <b>CE</b>	🗁 EN166 FT <b>C €</b>	Anti-scratch/Anti-fog
	Clear	RUSHPPSIG 📕	2C-1,2 🗁 1 FT KN CE	🗁 EN166 FT <b>C C</b>	Anti-scratch/Anti-fog
	Clear	RUSHPPSIB 📕	2C-1,2 🗁 1 FT KN CE	🗁 EN166 FT <b>C €</b>	Anti-scratch/Anti-fog
	Clear	RUSHPPSIY 📕	2C-1,2 🖆 1 FT KN CE	🗁 EN166 FT <b>CE</b>	Anti-scratch/Anti-fog +7
	Clear	RUSHPPSIO 📕	2C-1,2 🗁 1 FT KN CE	🗁 EN166 FT <b>C €</b>	Anti-scratch/Anti-fog +
	Kit foam & strap	RUSHKITFS	-	-	-
	Strap only	PSPRUS+-S01	-	-	-

# LENS MARKING

**Optical class symbols:** 

1. Continuous work

## Mechanical strength symbols:

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

### Others symbols:

K. Resistance to surface damage by fine particles

N. Resistance to fogging

C€ European standard ☐ Manufacturer name

## TECHNOLOGIES

### TWILIGHT

The new B-Twilight technology offers the advantages of ESP with a double anti-fog coating (on both sides of the lenses) to prevent fogging in the most challenging conditions.

Designed and used in low light conditions. it improves contrast. Its light transmission rate is perfect for outdoors, particularly morning and late earlv evening. B-Twilight fiters 76% of blue light.



Europe Bollé Safety 34 Rue de la Soie 69100 Villeurbanne - France Tél. : 00 33 (0) 4 78 85 23 64 Fax : 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc. F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s

- Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. C€ European standard ☐ Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

### 

The new exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

## CSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments. CSP is also combined with the exclusive PLATINUM®

coating that sustainably combats fogging.



U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY Tél. : 00 44 (0)208 391 4700 Fax: 00 44 (0)208 391 4733 e-mail : sales@bolle-safety.co.uk

# CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.





bolle-safety.com

# RUSH+ **PANORAMIC AND SPORTY**

CHARACTERISTICS			
LENSES	PC - 2,2 mm - Curve 9		
FRAME	-		
TEMPLES	PC + TPR		
STRAP	Nylon/15mm/Adjustable		
FOAM	SBR + Nylon		
SPARE LENSES	No		

PACKAGING AND EAN13 CODE								
	RUSHPPSI	RUSHPPSF	RUSHPTWI	RUSHPFSPSI	RUSHPPSIG	RUSHPPSIB	RUSHPPSIY	RUSHPPSIO
Individual plastic bag	3660740007041	3660740007058	3660740007065	3660740007577	3660740007157	3660740007171	3660740007140	3660740007164
10 safety spectacles per inner box	3660740107048	3660740107055	3660740107062	3660740107574	3660740107154	3660740107178	3660740107147	3660740107161
200 safety spectacles per outer pack	3660740207045	3660740207052	3660740207069	3660740207571	3660740207151	3660740207175	3660740207144	3660740207168

PACKAGING AND EAN13 CODE							
	RUSHPPSFY	RUSHPCSP	RUSHKITFS	PSPRUS+-S01			
Individual plastic bag	3660740007935	3660740008444	3660740006488	3660740007546			
20 foam and strap kits OR 40 foams only per inner box	3660740107932	3660740108441	3660740106485	3660740107543			
240 foam and strap kits OR 480 foams only per outer pack	3660740207922	3660740208448	3660740206482	3660740207540			







Europe Bollé Safety 34 rue de la Soie 69100 Villeurbanne - France Tél. : 00 33 (0) 4 78 85 23 64 Fax : 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY - UK Tél.: 00 44 (0)208 391 4700 Fax: 00 44 (0)208 391 4733 e-mail : sales@bolle-safety.co.uk



Non-contractual pictures

16/04/2020

bolle-safety.com