

SKYTEC™ | TRC705

A LIGHTWEIGHT PU COATED GLOVE WITH STEEL FIBRE AND RECYCLED POLYESTER

Outstanding cut resistance allowing protection in the most risky applications. PU coating protects the hand from abrasion and grease, delivering effective long lasting grip.

FEATURES

- › Cut resistant: Level E / ANSI A5
- › A flexible and comfortable glove offering great dexterity
- › HPPE on the inside provides comfort and protection
- › Fully encapsulated steel with recycled polyester on the outside strengthens the protection against burrs and sharp edges
- › PU coating gives exceptional abrasion resistance and sensitivity allowing workers to handle small pieces
- › Reinforced thumb crotch enhances durability
- › Seamless knit prevents irritation
- › RCS (Recycled Claim Standard) certified
- › 1 pair = 1PET bottle of 500ml recycled
- › 8g of CO₂ reduced vs virgin polyester alternative





CUT LEVEL
E



RECYCLED 100
claim standard



Part of the
Tricolore Range™




ECO

SUITABLE FOR


- | | |
|--|---|
| <p>Typical Industries</p> <ul style="list-style-type: none"> ▪ Automotive ▪ Construction ▪ Logistics ▪ Maintenance ▪ Manufacturing ▪ Metal Industry | <p>Suitable Applications</p> <ul style="list-style-type: none"> ▪ Assembly ▪ Handling sharp and greasy parts ▪ Machining ▪ Bodywork ▪ Precision mechanics ▪ Metal stamping |
|--|---|

CERTIFICATION

CAT II




EN 388:2016



4X43E

ANSI/ISEA 105



See overleaf for explanation

**PRODUCTION INFORMATION**

MATERIALS	LINER:	13 gauge HPPE, steel fibre, recycled polyester
	COATING:	Polyurethane (PU)
COLOUR	Green/black	
LENGTH (mm)	250 (Size Dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS	SKG00015EB	10 pairs per paper wrap
7/S	SKG00015ED	
8/M	SKG00015EF	
9/L	SKG00015EH	
10/XL	SKG00015EJ	120 pairs per case
11/XXL	SKG00015EL	

RECOMMENDATIONS FOR USE

- **USE:** General handling glove with cut protection. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS**MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS***

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE

Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

GLOBUS**EUROPE**

www.globusgroup.com

E: sales@globus.co.uk

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +971 4 882 9962

F: +971 4 882 9963

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

EU compliance certificate delivered by the notified body INTERTEK ITALIA SPA, Via Guido Miglioli, 2/A - 20063 Cernusco sul Naviglio (MI) - Italia (Notified Body No. 2575)