

STYLE REF: **3FW001M**
STYLE NAME: **3FEET WORK - MID**

Rock Fall®
INDUSTRY DEFINING SAFETY FOOTWEAR

SPECIFICATION: SUITABLE FOR REQUIREMENTS: ANTI-STATIC, ESD, EH | SIZE UK 2-13 (WHOLE SIZES)

ACTIV-STEP® 3FEET WORK FOOTBEDS ARE DESIGNED TO SUPPORT COMMON FOOT CONDITIONS WHICH INCLUDE: PLANTAR FASCIITIS, FATIGUE, ACHILLES TENDONITIS, PRONATION/SUPINATION INSTABILITIES AND BACK AND KNEE PAIN.

THEY HAVE BEEN SPECIFICALLY DESIGNED FOR INDUSTRIAL WORKPLACES AND INCLUDE ANTI-STATIC STITCHING AND TAPE FOR PRODUCT ASSURANCES PURPOSES.

THE FOOTBEDS ARE MULTI LAYERED AND BUILT UP TO OFFERED TAILORED ARCH SUPPORT BASED ON THE WEARERS FOOT TYPE.

3FW001M



Anti-static

Anti-static shoes have an electrical resistance between 0.1 and 1000 Mega Ohm (M), measured according to EN 20344: 2011 5 10. This value is a compromise between good protection from electrical shocks and sufficient dissipative capacity. These shoes may be worn in many different work environments.

ESD

ESD (Electrostatic Dissipative) shoes have an electrical resistance between 0.1 and 100 (M), measured according to BS EN 61340-4-3: 2002 (IEC 61340-4-3:2001). ESD shoes are thus guaranteed to have an extremely low electrical resistance under any conditions in order to prevent a strong, uncontrolled electrostatic charge.

EH

Non-conductive footwear often is classified with an "EH" rating. This safety standard is designed to provide a secondary source of protection when accidentally coming in contact with live electrical circuits to reduce the potential of electric shock.

SUBJECT TO CHANGE WITHOUT PRIOR NOTICE: 01/12/2019

WWW.ROCKFALL.COM | WWW.ROCKFALL.COM/PRODUCTS/3FEET-MID/
PROUDLY MANUFACTURED BY ROCK FALL UK, MAJOR HOUSE, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS