

# CONTOUR

## LIGHTWEIGHT AND EFFECTIVE

21 g of strength: sturdy, protective, stylish, comfortable and lightweight.  
CONTOUR is one of the top three best-selling models.

 PLATINUM



CONTPSI



CONTPSF



CONTESP



CONTPOL



PSSCONT-C10



21 g

**SUPPLIED WITH**

Microfibre pouch  
ETUIFS


















- + NON-SLIP BRIDGE**
- + NON-SLIP TIPGRIP TEMPLES**
- + ANTI-STATIC**

**bolle**  
SAFETY

# CONTOUR

## LIGHTWEIGHT AND EFFECTIVE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
<b>CONTOUR</b>	 Clear	CONTPSI	2C-1,2  1 FT KN €€	 EN166 FT €€	Anti-scratch/anti-fog (+P)
	 Smoke	CONTPSF	5-2,5  1 FT KN €€	 EN166 FT €€	Anti-scratch/anti-fog (+P)
	 ESP	CONTESP	5-1,4  1 FT €€	 EN166 FT €€	Anti-scratch
	 Polarized	CONTPOL	5-3,1  1 FT €€	 EN166 FT €€	Anti-scratch
	 CSP	PSSCONT-C10	5-1,4  1 FT KN €€	 EN166 FT €€	Anti-scratch/anti-fog (+P)

### LENS MARKING

#### Optical class symbols:

1. Continuous work

#### Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s


Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

#### Others symbols:

K. Resistance to surface damage by fine particles (optional)

N. Resistance to fogging (optional)

€€ European standard  Manufacturer name

### TECHNOLOGY

#### ESP

ESP, Extra Sensory Perception. An innovative coating to reduce dazzle and the harmful affects of blue light. ESP filters 57% of blue light, transmits 64% of visible light, 99.99% of UVA/UVB.

#### PLATINUM

This permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes. In all circumstances and at all times the PLATINUM lens innovation guarantees your eyes improved protection.

#### POLARIZED

A technology approved for permanent wear and certified with perfect optical quality, it offers unbeatable comfort by filtering glare and reflections. Ideal for the maritime environment. Filters 99.99% of UVA/UVB.

#### CSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments. CSP is also combined with the exclusive PLATINUM® coating that sustainably combats fogging.

### FRAME MARKING


**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for spectacles.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

K. Resistance to surface damage by fine particles (optional)

N. Resistance to fogging (optional)

€€ European standard  Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

### PACKAGING AND EAN13 CODE

	CONTPSI	CONTESP	CONTPSF	CONTPOL	PSSCONT-C10
Individual plastic bag	3660740003241	3660740003258	3660740003388	3660740000615	3660740009427
10 safety spectacles per inner box	3660740103248	3660740103255	3660740103385	3660740100612	3660740109424
240 safety spectacles per outer pack	3660740203245	3660740203252	3660740203382	3660740200619	3660740209421

### CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 8
FRAME	PC
TEMPLES	Nylon + TPE
STRAP	Non applicable
FOAM	Non applicable



10/06/2020

Europe Bollé Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

**bolle-safety.com**

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle**  
SAFETY